

tesa® 4611

Tunnel tape

PRODUCT INFORMATION

Product Description

tesa® 4611 is a strong acrylic coated cloth tape with a neutralized part of the adhesive side in the middle. It is based on a 120 mesh woven rayon fabric backing and a natural rubber adhesive. tesa® 4611 is an excellent solution for "Arts & Entertainment" applications.

Features:

- · high adhesion even on rough surfaces
- excellent tensile strength
- conformable
- easy to remove without residues
- no unpleasant smell
- very matt surface
- can be removed without leaving any residues from almost any surface
- available in black

The advantage of this tape vs. other tape solutions is the possibility to pull cables, cords or wires, even after fixing them on the surface.

Main Application

For cable fixing applications on stages, in the backstage areas in theaters, opera, concert halls, conventions and conferences.

Technical Data

- Backing material acrylic-coated cloth Temperature resistance (30 min) 140 °C
- Type of adhesive natural rubber Mesh 120 count per square inch
- Adhesion to steel 3.8 N/cm Surface finish matt

Properties

 Hand tearability Easy to write on yes Straight tear edges Abrasion resistance ++ ++ Easy to remove Water resistance ves

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

Additional Info

Recommendation: please conduct a test on the application surface before using the product.

For latest information on this product please visit http://l.tesa.com/?ip=04611

Page 1 of 1 / As of 07/04/14

tesa SE

Quickbornstraße 24 20253 Hamburg

http://www.tesa.com

Germany Phone: +49 (40) 4909 101

tesa tape inc.

5825 Carnegie Boulevard Charlotte, N.C. 28209 United States of America Tower 1 Singapore 138588 Phone: +1 (704) 554 0707 Tel: +65 6697 9888 Fax: +1 (704) 553 5634 Fax: +65 6659 6390 http://www.tesatape.com http://www.tesa-asia.com

tesa tape Asia Pacific Pte. Ltd. 9 North Buona Vista Drive

#04-01 The Metropolis

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.