

tesa® 53949 matt gaffer tape

Non-reflective polyethylene coated high grade cloth tape

PRODUCT INFORMATION

Product Description

tesa® 53949 is a matt gaffer tape specially designed for the arts and entertainment industry. It consists of a PE coated 80 mesh woven PET fabric backing coated with a pressure sensitive natural rubber adhesive.

tesa® 53949 is the ideal solution for a wide range of applications whenever a non-reflective surface is important.

Features:

- light-absorbing, non-reflective
- good adhesion, even on rough surfaces
- abrasion resistant
- water repellent
- conformable
- easy to remove

Main Application

- On-stage/back-stage jobs in theatre, opera, cinema and music halls
- Fixing of cables on carpets, walls etc.
- Covering of shiny and glossy surfaces
- Fixing of cable links
- Sealing of joints
- Floor marking and fixing

Technical Data

■ Backing material	PE extruded cloth	■ Tensile strength	85 N/cm
■ Total thickness	310 µm	■ Temperature resistance (30 min)	125 °C
■ Type of adhesive	natural rubber	■ Mesh	80 count per square inch
■ Adhesion to steel	2 N/cm	■ Surface finish	matt
■ Elongation at break	14 %		

Properties

■ Hand tearability	+	■ Abrasion resistance	+
■ Straight tear edges	+	■ Water resistance	+
■ Easy to remove	yes		

Evaluation across relevant tesa® assortment: ++ very good, + good, o medium, - low

For latest information on this product please visit <http://l.tesa.com/?ip=53949>

Page 1 of 1 / As of 08/09/14

tesa SE

Quickbornstraße 24
20253 Hamburg
Germany
Phone: +49 (40) 4909 101

tesa SE
A Beiersdorf Company

<http://www.tesa.com>

tesa tape inc.

5825 Carnegie Boulevard
Charlotte, N.C. 28209
United States of America
Phone: +1 (704) 554 0707
Fax: +1 (704) 553 5634
<http://www.tesatape.com>

tesa tape Asia Pacific Pte. Ltd.

9 North Buona Vista Drive
#04-01 The Metropolis
Tower 1
Singapore 138588
Tel: +65 6697 9888
Fax: +65 6659 6390
<http://www.tesa-asia.com>

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to advise you.