



- Standard 19" rack width per EIA standards.
- Standard rack depth front to rear rail is 29 1/4" and each lid is 4 1/2" deep.
- Standard with square rackmounting holes for cage nuts (not included) and aluminum cross components forming an "H" shaped rigid configuration.
- Easily adaptable to 10-32 tapped or 5/32" round (0.183") through holes.
- Unique "plug" style lid sealing system. Lids penetrate the body with an approximate 1" molded-in protrusion that provides outstanding sealing and anti-shear properties.
- Patent-pending compound hinge system allows the lids to swing out 270° and rest along the sides of the case or be easily removed and reinstalled in seconds.
- Front and rear doors are fitted with rubber gaskets for water resistant protection.
- Recessed heavy-duty twist latches allow these cases to meet most ATA and military specifications.
- Stacks securely with wheels on or off and this revolutionary design also allows for both lids to open completely while cases are stacked.
- All sizes come standard with 8 each HM-245 elastomeric, high damping, wide temperature range shock mounts with a load range of 40 to 150 lbs.
- Additional or stiffer shock mounts may be ordered from the factory and are easily field-installed.
- Standard high quality slide-in/out locking swivel 4" casters rated at 1,200 lbs.
- Automatic ambient pressure equalization valve (MIL-STD-648C).
- Black powder coated stainless steel key-lockable latches.
- Comfortable, spring-loaded, rubber over-molded handles.



Patent Pending





Standard dimensions front to rear rail: 29 1/4"

Part #	Rack Units	Height	Lid Depth
3SKB-R904U28	4 space	7"	4-1/2"
3SKB-R906U28	6 space	10-1/2"	4-1/2"
3SKB-R908U28	8 space	14"	4-1/2"
3SKB-R910U28	10 space	17-1/2"	4-1/2"



MUSIC PRODUCTS 800.410.2024 SPORTS PRODUCTS 800.654.5992 INDUSTRIAL PRODUCTS 800.783.0087